

View Online at <https://aerobasegroup.com/nsn/5925-01-138-9587>

Body Style:

Multipole-single actuator type

Body Length:

2.000 inches

Body Width:

2.170 inches

Body Height:

1.925 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

End Application:

6625nc614190p

Boss Height:

0.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 clip

Features Provided:

High inrush protection

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.525 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0