NSN 5925-01-138-9592

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-138-9592

Body Style: Single pole type **Body Length:** Between 2.490 inches and 2.510 inches **Body Width:** Between 0.740 inches and 0.760 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: Between 1.928 inches and 1.948 inches Center To Center Distance Between Terminals Parallel To Width: Between 0.740 inches and 0.760 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.052 inches and 2.072 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.740 inches and 0.760 inches **Fragility Factor:** Moderately rugged **End Application:** An/sqs53a ec7 **Boss Height:** Between 0.130 inches and 0.140 inches Mounting Surface To Terminal End Distance: Between 2.461 inches and 2.481 inches **Pole Quantity:** 1 Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 10.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 65.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 dc single location **Circuit Protection Type:** Overcurrent single location

NSN 5925-01-138-9592

Circuit Breaker - Page 2 of 2



Trip Release Method:
Magnetic-hydraulic single location
Trip Release Characteristic:
Instantaneous single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Shunt trip single location
Thread Size:
0.138 inches
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0