

View Online at <https://aerobasegroup.com/nsn/5925-01-139-0103>

Body Style:

Multipole-single actuator type

Body Length:

2.000 inches

Body Width:

1.540 inches

Body Height:

1.925 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Boss Height:

0.125 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 clip

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations and 5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations and 240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

20.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct all locations and 20.000 at 200 pct all locations

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0