

View Online at <https://aerobasegroup.com/nsn/5925-01-139-0103>

**Body Style:**

Multipole-single actuator type

**Body Length:**

2.000 inches

**Body Width:**

1.540 inches

**Body Height:**

1.925 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Boss Height:**

0.125 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 clip

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations and 5.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations and 240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

100.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

20.000 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

4.000 at 200 pct all locations and 20.000 at 200 pct all locations

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0