

View Online at <https://aerobasegroup.com/nsn/5925-01-139-3140>

**Body Length:**

11.000 inches

**Body Width:**

9.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

9.875 inches

**Center To Center Distance Between Terminals Parallel To Width:**

3.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

9.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

3.000 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.250 inches

**Mounting Surface To Terminal End Distance:**

9.281 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

250.0 amperes ac all locations and 250.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac second location and 250.0 dc second location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

20000.0 ac second location and 15000.0 dc second location

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+910.0/+1560.0 ac third location

**Internal Trip Release Configuration:**

Shunt trip third location

**Thread Size:**

0.250 inches

**Frequency In Hertz:**

60.0 third location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0