## NSN 5925-01-139-6098

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-139-6098

Body Style:
Multipole-single actuator type
Body Length:
10.125 inches
Body Width:
8.250 inches
Body Height:
3.812 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
7.750 inches
Center To Center Distance Between Terminals Parallel To Width:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
7.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.750 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.187 inches
Pole Quantity:
3
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Cubic Measure:
318.421 cubic inches
Maximum Continuous Load Current Rating Per Pole:
250.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
00000 0

22000.0 ac all locations

## **NSN 5925-01-139-6098** Circuit Breaker - Page 2 of 2



Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1200.0/+4000.0 ac all locations
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
18.000 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0