

View Online at <https://aerobasegroup.com/nsn/5925-01-143-2451>

Body Style:

Single pole type

Body Length:

6.312 inches

Body Width:

1.375 inches

Body Height:

3.187 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.874 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.874 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.125 inches

Boss Height:

0.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac single location and 250.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac single location and 10000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

70.000 at 200 pct single location and 425.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0