## NSN 5925-01-143-2451

Circuit Breaker - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5925-01-143-2451

Single pole type
Body Length:
6.312 inches
Body Width:
1.375 inches
Body Height:
3.187 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
4.874 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.874 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.125 inches
Boss Height:
0.250 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac single location and 15.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac single location and 250.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
14000.0 ac single location and 10000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal-magnetic single location

140.0 single location

**Trip Release Characteristic:** 

Instantaneous single location and time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

**Reset Method:** 

Manual

## NSN 5925-01-143-2451

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
70.000 at 200 pct single location and 425.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0