NSN 5925-01-143-8385



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-143-8385 **Body Style:** Single pole type **Body Length:** 2.150 inches **Overall Diameter:** 0.750 inches **Case Material:** Plastic **End Application:** 4110-01-077-8253 **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 4.0 amperes ac single location and 4.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location and 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location and 200.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 push button **Actuator Function:** Reset **Actuator Position Designation:**

At pole one

Internal Trip Release Configuration:

Series trip single location

NSN 5925-01-143-8385

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct single location and 10.000 at 200 pct single location

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0