NSN 5925-01-146-1293

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-146-1293

Overall	Length:

- 4.090 inches
- **Overall Height:**
- 1.580 inches
- **Overall Width:**
- 3.940 inches

Case Material:

Plastic

Switch Contact Arrangement:

Single pole, double throw

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

300.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

NSN 5925-01-146-1293

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration: Series trip single location **Switch Location And Position Designation:** Internal at pole one Trip Delay Time In Seconds Per Rated Continuous Current: 100.000 at 250 pct single location **Inclosure Protection Type For Which Designed:** Corrosion resistant and fungus resistant and humidity resistant **Trip Release Ambient Tempurature Rating:** 70.0 degrees fahrenheit single location Switch Terminal Type: Tab, solder lug Switch Current Rating And Type In Amps: 5.0 dc Switch Voltage Rating And Type In Volts: 28.0 dc **Unpackaged Unit Weight:** 30.000 ounces **Test Data Document:** 80063-sm-a-317335 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0