NSN 5925-01-147-8848

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-147-8848

| Body Style: |
|--|
| Multipole-multiple actuator type |
| Body Length: |
| 4.750 inches |
| Body Width: |
| 3.093 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 3.550 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 1.026 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.750 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.026 inches |
| Boss Height: |
| 0.219 inches |
| Mounting Surface To Terminal End Distance: |
| 3.484 inches |
| Pole Quantity: |
| 3 |
| Mounting Facility Type And Quantity: |
| 6 threaded hole |
| Storage Type: |
| General purpose warehouse |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 3.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 480.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 5000.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Magnetic-hydraulic all locations |
| Trip Release Characteristic: |
| Time delay all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |

125.0 all locations

NSN 5925-01-147-8848 Circuit Breaker - Page 2 of 2

