

View Online at <https://aerobasegroup.com/nsn/5925-01-148-3124>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

Between 2.200 inches and 2.800 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.938 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.062 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

Between 2.409 inches and 2.533 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes dc third location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac first location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 dc third location

**Circuit Protection Type:**

Undervoltage third location

**Trip Release Method:**

Magnetic-hydraulic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

120.0 ac first location

**Trip Release Characteristic:**

Time delay first location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series/relay trip first location

**Thread Size:**

0.138 inches

**Trip Release Duty Cycle:**

Intermittent first location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 200 pct first location and 20.000 at 200 pct first location

**Inclosure Protection Type For Which Designed:**

Fungus resistant and moisture resistant

**Frequency In Hertz:**

50.0 second location or 60.0 second location

**Unpackaged Unit Weight:**

9.500 ounces

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0