

View Online at <https://aerobasegroup.com/nsn/5925-01-148-4478>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

0.920 inches

Body Height:

1.770 inches

Case Material:

Plastic

Switch Contact Arrangement:

Single pole, double throw

Boss Height:

0.125 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 clip

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.200 single location and 7.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct single location and 0.950 at 200 pct single location and 0.020 at 400 pct single location and 0.240 at 400 pct single location and 0.002 at 800 pct single location and 0.060 at 800 pct single location

Switch Terminal Type:

Turret

Switch Current Rating And Type In Amps:

5.0 dc

Switch Voltage Rating And Type In Volts:

28.0 dc

Special Features:

Handle equipped with internally mtd led, 24-32 vdc, red; handle color black; body color gray

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0