NSN 5925-01-149-9352

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-149-9352

Body Style:

Single pole type

Overall Length:

2.280 inches

Overall Width:

0.450 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.137 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.970 inches

Switch Contact Arrangement:

Single pole, double throw

Boss Height:

0.177 inches

Mounting Surface To Terminal End Distance:

2.110 inches

Pole Quantity:

.

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

 $5.0 \ \text{amperes}$ ac single location and $5.0 \ \text{amperes}$ dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

200.0 ac single location and 200.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-149-9352 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 push button
Actuator Function:
Trip w/separate reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
30.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
70.0 degrees fahrenheit single location
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
1.0 ac and 1.0 dc
Switch Voltage Rating And Type In Volts:
250.0 ac and 65.0 dc
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
1.160 ounces
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0