## NSN 5925-01-150-4464

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-150-4464

**Body Style:** 

Rectangular dimensional envelope

**Overall Length:** 

Between 1.990 inches and 2.010 inches

**Overall Height:** 

Between 1.365 inches and 1.385 inches

Overall Width:

Between 1.740 inches and 1.760 inches

**Case Material:** 

Metal

**Unthreaded Mounting Hole Diameter:** 

Between 0.210 inches and 0.230 inches

**Fragility Factor:** 

Moderately rugged

**Pole Quantity:** 

2

**Arc Quenching Method:** 

Magnetic blowout

**Mounting Facility Type And Quantity:** 

2 terminal

**Storage Type:** 

General purpose warehouse

**Special Handling Feature:** 

Magnetic

**Maximum Continuous Load Current Rating Per Pole:** 

50.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

24.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Thermal all locations

**Trip Release Characteristic:** 

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

125.0 all locations

**Reset Method:** 

Automatic

**Internal Trip Release Configuration:** 

Series trip all locations

## NSN 5925-01-150-4464

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed:
Hermetically sealed
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0