

View Online at <https://aerobasegroup.com/nsn/5925-01-153-0144>

Body Style:

Multipole-single actuator type

Overall Height:

11.469 inches

Body Length:

12.000 inches

Body Width:

9.000 inches

Case Material:

Plastic

Switch Contact Arrangement:

Double pole, single throw, normally open

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

175.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Auxiliary Trip Coil Voltage Type And Rating In Volts:

120.0 dc all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

External Actuator Linkage Arrangement:

One, two, and three linked

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip w/remote trip feature all locations

Trip Release Duty Cycle:

Intermittent all locations

Switch Location And Position Designation:

Internal at pole one

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Switch Terminal Type:

Compression

Switch Current Rating And Type In Amps:

15.0 ac

Switch Voltage Rating And Type In Volts:

250.0 ac

Special Features:

Mounting hardware included

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

30.500 pounds

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0