NSN 5925-01-153-0144

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-153-0144

Body Style:
Multipole-single actuator type
Overall Height:
11.469 inches
Body Length:
12.000 inches
Body Width:
9.000 inches
Case Material:
Plastic
Switch Contact Arrangement:
Double pole, single throw, normally open
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 clip
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
175.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Auxiliary Trip Coil Voltage Type And Rating In Volts:
120.0 dc all locations
Trip Release Characteristic:
Time delay all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-153-0144 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
External Actuator Linkage Arrangement:
One, two, and three linked
Auxiliary Switch Function And Quantity:
1 control
Internal Trip Release Configuration:
Series trip w/remote trip feature all locations
Trip Release Duty Cycle:
Intermittent all locations
Switch Location And Position Designation:
Internal at pole one
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Switch Terminal Type:
Compression
Switch Current Rating And Type In Amps:
15.0 ac
Switch Voltage Rating And Type In Volts:
250.0 ac
Special Features:
Mounting hardware included
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
30.500 pounds
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0