NSN 5925-01-154-2468

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-154-2468 **Body Style:** Single pole type **Body Length:** 3.250 inches **Body Width:** 1.000 inches **Body Height:** 2.500 inches **Case Material:** Plastic **End Application:** 5410-01-073-3189 **Boss Height:** 0.219 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 40.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:**

1 toggle **Actuator Function:** Trip-reset

NSN 5925-01-154-2468

Circuit Breaker - Page 2 of 2

No Fiig: A030a0



Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
1 clip and 1 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: