NSN 5925-01-155-7697



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-155-7697 **Body Style:** Single pole type **Body Length:** 2.000 inches **Body Width:** 0.920 inches **Body Height:** 1.770 inches **Case Material: Plastic Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity: Maximum Continuous Load Current Rating Per Pole:** 2.5 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:**

At pole one

Internal Trip Release Configuration:

Series trip single location

NSN 5925-01-155-7697

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 200 pct single location and 9.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

,

Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0