

View Online at <https://aerobasegroup.com/nsn/5925-01-155-9583>

Body Style:

Rectangular dimensional envelope

Overall Length:

191.0 millimeters

Overall Height:

106.0 millimeters

Overall Width:

109.0 millimeters

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 rotary

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Inclosure Protection Type For Which Designed:

Corrosion resistant and dusttight

Trip Release Ambient Temperature Rating:

20.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0