NSN 5925-01-156-7530



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-156-7530 **Body Style:** Rectangular dimensional envelope **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 6 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Unpackaged Unit Weight:** 8.000 pounds **Precious Material And Location:** Contacts silver **Precious Material:** Silver

N/a

Shelf Life:

NSN 5925-01-156-7530

Circuit Breaker Tripper - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A030a0