

View Online at <https://aerobasegroup.com/nsn/5925-01-157-4598>

Body Style:

Multipole-single actuator type

Bushing Length:

0.390 inches

Body Length:

2.050 inches

Body Width:

2.270 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.550 inches

Center To Center Distance Between Terminals Parallel To Width:

0.755 inches

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.661 inches

Nonturn Device Length:

0.150 inches

Nonturn Device Diameter:

0.161 inches

End Application:

6920-01-128-1306

Mounting Surface To Terminal End Distance:

2.240 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 150.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

47.0 all locations or 63.0 all locations

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0