

View Online at <https://aerobasegroup.com/nsn/5925-01-157-4598>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.390 inches

**Body Length:**

2.050 inches

**Body Width:**

2.270 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.550 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.755 inches

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.661 inches

**Nonturn Device Length:**

0.150 inches

**Nonturn Device Diameter:**

0.161 inches

**End Application:**

6920-01-128-1306

**Mounting Surface To Terminal End Distance:**

2.240 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 150.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Frequency In Hertz:**

47.0 all locations or 63.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0