

View Online at <https://aerobasegroup.com/nsn/5925-01-157-6632>

**Body Style:**

Single pole type

**Overall Length:**

50.8 millimeters

**Body Width:**

24.14 millimeters

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

16.3 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

39.98 millimeters

**End Application:**

3805-01-126-7915

**Mounting Surface To Terminal End Distance:**

32.5 millimeters

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac single location and 3.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

110.0 ac single location and 30.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

600.0 ac single location and 600.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

130.0 single location

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.164 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

5.500 at 200 pct single location and 55.000 at 200 pct single location

**Inclsoure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0