

View Online at <https://aerobasegroup.com/nsn/5925-01-158-4168>

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes dc second location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc second location

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

6.000 first location and 50.000 first location

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

6.000 at 125 pct first location and 50.000 at 125 pct first location and 0.900 at 200 pct first location and 4.000 at 200 pct first location and 0.010 at 400 pct first location and 0.090 at 400 pct first location and 0.004 at 800 pct first location and 0.018 at 800 pct first location

**Frequency In Hertz:**

400.0 first location

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0