

View Online at <https://aerobasegroup.com/nsn/5925-01-159-5236>

Bushing Length:

Between 0.332 inches and 0.380 inches

Body Length:

Between 1.531 inches and 1.562 inches

Body Width:

Between 1.906 inches and 1.937 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.875 inches and 0.906 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.594 inches and 0.656 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

Between 1.797 inches and 1.828 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Features Provided:

High inrush protection

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac all locations and 7.5 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations and 500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Switch Location And Position Designation:

Internal at pole three

Trip Delay Time In Seconds Per Rated Continuous Current:

0.055 at 200 pct all locations and 0.950 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and hermetically sealed

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

0.5 ac and 0.5 dc

Switch Voltage Rating And Type In Volts:

120.0 ac and 50.0 dc

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

150.0 grams

Test Data Document:

81349-mil-c-39019 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire hook

Specification Data:

81349-mil-c-39019/6 government specification

Shelf Life:

Nil

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0