NSN 5925-01-160-9069

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-160-9069

Body Style:
Multipole-multiple actuator type
Body Length:
2.502 inches
Body Width:
3.000 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.940 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.060 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.250 inches
Boss Height:
0.150 inches
Mounting Surface To Terminal End Distance:
2.475 inches
Pole Quantity:
4
Mounting Facility Type And Quantity:
8 threaded hole
8 threaded hole Maximum Continuous Load Current Rating Per Pole:
Maximum Continuous Load Current Rating Per Pole:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic: Time delay all locations
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic: Time delay all locations Reset Method:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Manual Actuator Type And Quantity:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Manual Actuator Type And Quantity: 4 toggle
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Manual Actuator Type And Quantity: 4 toggle Actuator Function:
Maximum Continuous Load Current Rating Per Pole: 5.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic all locations Trip Release Characteristic: Time delay all locations Reset Method: Manual Manual Actuator Type And Quantity: 4 toggle Actuator Function: Trip-reset

Thread Size: 0.138 inches

NSN 5925-01-160-9069

Circuit Breaker - Page 2 of 2



Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
8 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0