NSN 5925-01-161-9292



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-161-9292 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.380 inches **Body Length:** 1.500 inches **Body Width:** 1.250 inches **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.625 inches **Nonturn Device Length:** 0.130 inches **Nonturn Device Diameter:** 0.140 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.780 inches **Pole Quantity: Arc Quenching Method:**

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

NSN 5925-01-161-9292

Circuit Breaker - Page 2 of 2

A030a0



Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations and 1000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.900 at 200 pct all locations and 4.500 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
No
Fiig: