## NSN 5925-01-162-4598

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-162-4598 **Body Style:** Rectangular dimensional envelope **Overall Length: 7.375** inches **Overall Height:** 4.000 inches **Overall Width:** 4.250 inches **Unthreaded Mounting Hole Diameter:** 0.312 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 1.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 440.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations or 400.0 all locations **Test Data Document:** 81349-mil-m-24347 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 6 screw **Specification Data:** 81349-mil-m-24347 government specification

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5925-01-162-4598

Circuit Breaker Tripper - Page 2 of 2



Demilitarization:

No

Fiig:

A030a0