## NSN 5925-01-163-2493

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-163-2493

Body Length:
5.125 inches
Body Width:
3.108 inches
Body Height:
3.360 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
3.550 inches
Center To Center Distance Between Terminals Parallel To Width:
1.026 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.026 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.220 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 threaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Features Provided:
High inrush protection
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
75.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:

Magnetic-hydraulic all locations

## NSN 5925-01-163-2493

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.300 at 200 pct all locations and 1.500 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
2.000 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0