

View Online at <https://aerobasegroup.com/nsn/5925-01-163-9088>

Body Style:

Single pole type

Body Length:

0.740 inches

Body Width:

0.430 inches

Body Height:

1.360 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

End Application:

4920-01-066-4155

Boss Height:

0.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location and 3.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

30.0 ac single location and 30.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct single location and 10.000 at 200 pct single location

Trip Release Ambient Temperature Rating:

50.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0