NSN 5925-01-165-2913

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-165-2913

Body Style: Rectangular dimensional envelope **Overall Length:** Between 1.235 inches and 1.265 inches **Overall Height:** Between 0.425 inches and 0.455 inches Overall Width: 0.500 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **End Application:** 2320-01-121-2102 **Pole Quantity: Mounting Facility Type And Quantity:** 2 clip Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 6.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 12.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Automatic **Inclosure Protection Type For Which Designed:** General purpose

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

NSN 5925-01-165-2913

Circuit Breaker - Page 2 of 2



Frequency lı	n Hertz:
--------------	----------

60.0 single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0