

View Online at <https://aerobasegroup.com/nsn/5925-01-166-7560>

Body Style:

Multipole-single actuator type

Body Length:

2.000 inches

Body Width:

2.170 inches

Body Height:

1.770 inches

Case Material:

Plastic

Boss Height:

0.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 clip

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

0.200 all locations and 7.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct all locations and 1.000 at 200 pct all locations and 0.020 at 400 pct all locations and 0.230 at 400 pct all locations and 0.005 at 800 pct all locations and 0.090 at 800 pct all locations

Special Features:

Handle equipped w/neon bulb; flush mtg hardware incl

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0