

View Online at <https://aerobasegroup.com/nsn/5925-01-166-9675>

**Body Length:**

Between 7.115 inches and 7.135 inches

**Body Width:**

Between 4.490 inches and 4.510 inches

**Body Height:**

Between 2.958 inches and 2.978 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 2.797 inches and 2.827 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.500 inches

**Unthreaded Mounting Hole Diameter:**

0.031 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 4.638 inches and 4.668 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.490 inches and 1.510 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.208 inches and 0.228 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 threaded hole and 6 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

150.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac third location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip w/dual rating first location

**Thread Size:**

0.190 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

15.000 at 200 pct all locations and 95.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant and moisture resistant

**Frequency In Hertz:**

47.0 all locations or 63.0 all locations

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0