

View Online at <https://aerobasegroup.com/nsn/5925-01-168-9670>

**Body Style:**

Single pole type

**Body Length:**

2.499 inches

**Body Width:**

1.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

2.124 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.062 inches

**Boss Height:**

0.156 inches

**Mounting Surface To Terminal End Distance:**

2.531 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded stud

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic-hydraulic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.190 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

150.000 at 125 pct single location

**Thread Tolerance Class:**

2a external

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0