

View Online at <https://aerobasegroup.com/nsn/5925-01-170-1532>

Body Style:

Multipole-multiple actuator type

Body Length:

Between 2.468 inches and 2.532 inches

Body Width:

Between 2.968 inches and 3.032 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.906 inches and 1.970 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.722 inches and 0.782 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.030 inches and 2.094 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.722 inches and 0.782 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.108 inches and 0.172 inches

Mounting Surface To Terminal End Distance:

Between 2.688 inches and 2.752 inches

Pole Quantity:

4

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

8 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

6.0 amperes ac fourth location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

4 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, three, and four linked

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Switch Location And Position Designation:

Internal at pole four

Trip Delay Time In Seconds Per Rated Continuous Current:

0.180 at 200 pct all locations and 1.800 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and humidity resistant and moisture resistant and shock resistant and vibration resistant

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

10.0 ac and 5.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 30.0 dc

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0