

View Online at <https://aerobasegroup.com/nsn/5925-01-170-2272>

Body Style:

Multipole-single actuator type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

1.281 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

500.0 milliamperes ac first location500.0 milliamperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac first location240.0 ac second location12.0 dc third location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac first location1000.0 ac second location1000.0 dc third location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay first locationtime delay second locationinstantaneous third locationtime delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations



Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.055 at 200 pct first location and 0.950 at 200 pct first location0.055 at 200 pct second location and 0.950 at 200 pct second location

Inclosure Protection Type For Which Designed:

Hermetically sealed and shockproof and vibrationproof

Special Features:

Pole three is a switch

Frequency In Hertz:

60.0 first location or 400.0 first location60.0 second location or 400.0 second location

Unpackaged Unit Weight:

3.600 ounces

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0