

View Online at <https://aerobasegroup.com/nsn/5925-01-170-2306>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

0.920 inches

Body Height:

1.770 inches

Case Material:

Plastic

Switch Contact Arrangement:

Single pole, double throw

Boss Height:

0.125 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 clip

Maximum Continuous Load Current Rating Per Pole:

1.5 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.200 single location and 7.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Switch Location And Position Designation:

External at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct single location and 0.950 at 200 pct single location and 0.020 at 400 pct single location and 0.240 at 400 pct single location

Switch Terminal Type:

Turret

Switch Current Rating And Type In Amps:

3.0 dc

Switch Voltage Rating And Type In Volts:

50.0 dc

Special Features:

Flush mtg hardware incl; illuminated handle

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0