NSN 5925-01-171-3636

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-171-3636

Body Style:
Multipole-single actuator type
Bushing Length:
0.495 inches
Body Length:
2.000 inches
Body Width:
1.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.530 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Switch Contact Arrangement:
Single pole, double throw
Mounting Surface To Terminal End Distance:
2.232 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
2.5 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
65.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations

NSN 5925-01-171-3636 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.500 inches
Switch Location And Position Designation:
Internal at pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct all locations and 20.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
10.0 ac and 3.0 dc
Switch Voltage Rating And Type In Volts:
250.0 ac and 50.0 dc
Thread Series Designator:
Un
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0