NSN 5925-01-172-7243

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-172-7243

Thread Pitch Diameters:
+0.3503/+0.3537 inches
Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.500 inches
Body Width:
1.250 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.875 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Switch Contact Arrangement:
Single pole, double throw
Mounting Surface To Terminal End Distance:
1.780 inches
Pole Quantity:
2
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
20.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

NSN 5925-01-172-7243

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
'
Actuator Position Designation:
Between pole one and two
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
0.900 at 200 pct all locations and 4.500 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Switch Terminal Type:
Pin
Switch Current Rating And Type In Amps:
10.0 ac
Switch Voltage Rating And Type In Volts:
250.0 ac
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0