

View Online at <https://aerobasegroup.com/nsn/5925-01-172-8510>

Body Style:

Single pole type

Bushing Length:

Between 0.250 inches and 0.265 inches

Body Length:

2.189 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.160 inches and 2.220 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.900 inches and 0.910 inches

Mounting Surface To Terminal End Distance:

Between 2.340 inches and 2.400 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location and 20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

6000.0 ac single location and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

19.000 at 200 pct single location and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant and sand resistant and dusttight and corrosion resistant and humidity resistant and fungus resistant and explosion resistant

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

3.250 ounces

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab w/screw

Specification Data:

53711-5433036 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0