

View Online at <https://aerobasegroup.com/nsn/5925-01-173-1113>

Body Style:

Single pole type

Bushing Length:

0.125 inches

Body Length:

2.187 inches

Body Width:

0.812 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.560 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.875 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 20.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

50.0 single location or 60.0 single location

Unpackaged Unit Weight:

2.500 ounces

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A030a0