

View Online at <https://aerobasegroup.com/nsn/5925-01-174-1562>

Body Style:

Multipole-multiple actuator type

Body Length:

5.750 inches

Body Width:

2.000 inches

Body Height:

2.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.624 inches

Center To Center Distance Between Terminals Parallel To Width:

0.968 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

End Application:

Medium intensity approach lighting system, fa8767 (mals)

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 terminal

Maximum Continuous Load Current Rating Per Pole:

60.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

1.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 125 pct all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0