

View Online at <https://aerobasegroup.com/nsn/5925-01-174-8585>

Body Style:

Multipole-multiple actuator type

Bushing Length:

Between 0.235 inches and 0.265 inches

Body Length:

Between 1.985 inches and 2.015 inches

Body Width:

Between 2.260 inches and 2.270 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.515 inches and 1.545 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.735 inches and 0.765 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.647 inches and 1.677 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.735 inches and 0.765 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.390 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Auxiliary Trip Coil Voltage Type And Rating In Volts:

250.0 ac first location

Trip Release Characteristic:

Time delay third location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series/relay trip first location

Thread Size:

0.138 inches

Trip Release Duty Cycle:

Continuous first location

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct third location and 20.000 at 200 pct third location

Inclosure Protection Type For Which Designed:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Special Features:

Rocker actuator attached to circuit breaker handle

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0