

View Online at <https://aerobasegroup.com/nsn/5925-01-175-5048>

**Body Style:**

Multipole-single actuator type

**Body Length:**

14.000 inches

**Body Width:**

8.969 inches

**Body Height:**

4.531 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

10.688 inches

**Center To Center Distance Between Terminals Parallel To Width:**

3.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

10.688 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

3.000 inches

**Boss Height:**

0.515 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

18

**Maximum Continuous Load Current Rating Per Pole:**

300.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

42000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

130.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Thread Size:**

0.312 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

600.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Moisture resistant

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A030a0