NSN 5925-01-175-8200

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-175-8200

Body Style:

Single pole type

Body Length:

Between 3.209 inches and 3.229 inches

Body Width:

Between 1.459 inches and 1.479 inches

Body Height:

Between 2.646 inches and 2.666 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 2.365 inches and 2.385 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.303 inches and 1.323 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.115 inches and 0.135 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

NSN 5925-01-175-8200 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.250 at 200 pct single location and 1.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0