NSN 5925-01-175-8204

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-175-8204 **Body Style:** Single pole type **Body Length:** 3.500 inches **Body Width:** 0.969 inches **Body Height:** 2.312 inches **Case Material: Plastic Boss Height:** 0.188 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 35.0 amperes ac single location and 35.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 125.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location and 2500.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

Actuator Position Designation:

At pole one

NSN 5925-01-175-8204

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 210.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Test Data Document:

81349-mil-c-17588 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 quick disconnect, female

Specification Data:

81349-mil-c-17588 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Deminitar ization

No

Fiig:

A030a0