

View Online at <https://aerobasegroup.com/nsn/5925-01-177-3177>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.000 inches

Overall Height:

1.320 inches

Overall Width:

1.777 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 clamp

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Features Provided:

Current limiter

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct all locations and 0.900 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Unpackaged Unit Weight:

0.180 ounces

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0