

View Online at <https://aerobasegroup.com/nsn/5925-01-179-9487>

**Case Material:**

Plastic

**Switch Contact Arrangement:**

Single pole, double throw

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

500.0 milliamperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

130.0 dc all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

0.500 all locations and 6.500 all locations

**Manual Actuator Type And Quantity:**

1 toggle

**Auxiliary Switch Function And Quantity:**

1 alarm

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.130 at 200 pct all locations and 1.200 at 200 pct all locations and 0.031 at 400 pct all locations and 0.220 at 400 pct all locations and 0.011 at 600 pct all locations and 0.110 at 600 pct all locations

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0