NSN 5925-01-181-4736

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-181-4736

Body Style:
Rectangular dimensional envelope
Overall Length:
2.360 inches
Overall Height:
1.240 inches
Overall Width:
2.130 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.190 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
50.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 all locations
Reset Method:
Automatic
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct all locations and 45.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant

r unguo roolotan

Frequency In Hertz:

400.0 all locations

NSN 5925-01-181-4736

Circuit Breaker - Page 2 of 2



Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0